GDP (Gel Dispensing Printing) method 3D printer



3DGD-1800

Innovating sign graphics creation with large-scale and high-speed 3D printing

Mimaki 3DGD-1800

Max. size:
1800mm
Large-scale
3D print

Unparalleled printing speed

High-speed 3D printer builds objects at 350 vertical mm/hour

Utilization of 3D data broadens the potential for application

Hollow objects allowing easy processing

A life-size* 3D object can be completed in 7 hours.

*object size W x L x H : 600 x 600 x 1,800 (mm)

Easily print large-sized 3D objects

Objects up to 1,800mm in height can be printed. Assembling multiple prints allows for the creation of extra-large objects, exceeding the printable area.

Unparalleled printing speed

The product adopts the "Gel Dispensing Printing" technology which extrudes a UV curable gel-type resin lineally, fusing layers by instantly curing the resin with ultraviolet object is printed in irradiation. Unlike 3D fused deposition modeling (FDM) involving the thermal treatment of resin, the product is capable of

creating objects swiftly. It also allows the production of two different objects simultaneously using dual print-heads. The 3D printer can create 3D objects in about 1/3 the time of conventional handcrafting, allowing much faster production than manual methods and significantly reducing the production time when 3D data is available.

Hollow objects allowing easy processing

The printed 3D objects are extremely light in spite of their large size because they are hollow. It is also possible to increase the strength by adding armatures and reinforcement materials to the hollowed-out interior. As the printed objects are white in color and translucent, you can also create internally illuminated signage housing LED modules and other light sources.



Channel letters

Internally illuminated signage


Utilization of 3D data broadens the potential for application

If you have 3D data, you can create objects in varying sizes. Unlike handcrafting, 3D printing allows you to use a 3D data to share an image of the object and its installation with the customer from the design stage.

With 3D data, objects can be printed in various sizes.







Combination with Mimaki inkjet printers further expands the power of expression

Max size:

1800mm

Utilizing inkjet printers to apply decorative finishes to 3D objects or combining outputs of both technologies enables the production of an object with higher impact that can be used for large three-dimensional signboards, life-sized displays, creative art etc. Furthermore, combining the 3DGD-1800 with a 3D scanner, it is possible to create 3D copies of an existing object. Utilization of digital 3D data opens up the possibilities of expression.

■Surface imaging using Mimaki printers

■Production processes of 3DGD-1800 and post-processing (example) Post-processing *1 (Polishing/coating)





nforcement/surface decoration

Installation



*1: Post-processing equipment sold separately





*2: A 3D scanner is separately required as the 3DGD-1800 does not have a scan function

■Specifications

3DGD-1800								
3D printing method	Gel Dispensing Printing / Dual print		Nozzle size (dia.)	1.8 mm / 2.6 mm (Replaceable)	Operating	Power	3 x 25A, 380-400 VAC ±10%, 50 / 60Hz	
Print head	2		Printing speed	Height 350 mm/h (13.8 in/h)	specifications	Air pressure	600 to 800 kPa	
Max. printing size	WxDxH	1,450x1,110x1,800 mm (57.1x43.7x70.9 in)	Printing material	MG-100W (White UV curable resin)		Power consumption	10kW (Printing)	
	Weight Normal	150 kg (330.7 lb)	3D data format	stl, obj, 3ds, ply, blend		Temperature	16 to 30 degC. 60.8 to 86 degF.	
Layer pitch	Quality	1.0 mm	Slicer software	3DGD Slicer	Outside dimensions	WxDxH	3,000x2,200x2,800 mm (118.1x86.6x110.2 in)	
	High resolution	0.8 mm	Interface	Ethernet	Weight	2,500 kg (5,511.5 lb)		

■Software, Suppliesions

Item	Code	Remark		
3DGD Slicer	(TBD)	Slicer software		
3D printer ink MG100	MG100-W-BS-1-RA	19 kg bottle		



Precautions for 3D objects

·Please make sure to execute an advanced evaluation regarding the physical property (strength, weather resistance, safety etc.) for estimated applications.

Safety notice

Ultraviolet (UV) irradiation equipment is mounted on this product. You are dealing with UV light sources that may harm your health. Please follow below guidelines strictly.

Do not look directly into the UV light source nor place your hand, or expose your skin directly to the UV light source.

- •Please make sure the room is well ventilated due to smells partially accompanying with 3D modeling •In acilition, please be sure to read the instructions and guidelines of the manual carefully to follow.
- Some of samples in this catalog are artificial renderings. Specifications, design and dimensions stated in this catalog may be subject to change without notice for technical improvements etc. The corporate names and merchandise names written in this catalog are the trademark or registered trademark of the respective corporations.
- The specifications described in this catalog are as of July 2020.



MIMAKI ENGINEERING CO., LTD.

2182-3 Shigeno-Otsu, Tomi-city, Nagano 389-0512, Japan TEL:+81-268-64-2281

Mimaki Global Network

Singapore MIMAKI SINGAPORE PTE. LTD.

MIMAKI USA, INC. USA MIMAKI BRASIL COMERCIO E IMPORTACAO LTDA Brazil MIMAKI INDIA PRIVATE LIMITED India Taiwan MIMAKI ENGINEERING (TAIWAN) CO.,LTD

MIMAKI EUROPE B.V. Europe PT. MIMAKI INDONESIA Indonesia Australia MIMAKI AUSTRALIA PTY. LTD. China SHANGHAI MIMAKI TRADING CO., LTD. MIMAKI (THAILAND) CO.,LTD. Thailand